

TECHNICAL DATA SHEET– V1/2023

STAINLESS STEEL CONVEX MIRROR “ANTI-FREEZE” VERSION



Stainless Steel Convex Mirror – “Anti-Freeze” version		
DIMENSION (mm)		Ø600 mm
ITEM CODE		CMCH15Z860STA0
LENS	MATERIAL	SUS 304
	THICKNESS (MM)	0.5
	TOLERANCE (MM)	+/- 0.05
	REFLECTION	> 60%
	RADIUS (R')	2200
	TOLERANCE	+/- 5%
	FIELD OF VISION- RANGE (L~U MM)	570~600
	TOLERANCE (MM)	- 30
	Resistant to salty marine environment – see test report num 28109082 001 dated 01/04/2016	
FRAME AND BACK PLATE	MATERIAL	ABS Plastic – UV resistant and shockproof
	REFLECTIVE	3M™ Diamond Grade™ DG3 Series 4000 / red
THERMOGEL TECHNOLOGY	- Prevents and limits ice formation on the lens surface. - The thermoactive gel between the lens and rear panel regulates the temperature of the mirror surface according to the outside temperature. - No electric connection / power supply required. - Correct operation depends on external environmental conditions and may be limited by excessive humidity, lack of exposure to sunlight, or temperatures below –20°C.	
UNIT WEIGHT	KG	15.00
SUPPORTS	MATERIAL	Raw Steel
	COATING	Hot-dip galvanizing (HDG)
	POLE DIAMETER (MM)	60 o 76
	WEIGHT (KG)	Ø 60 = 1,12 Ø 76 = 1,25