

Stainless steel convex mirror

DIMENSION (mm): 600x800 | ITEM CODE: CMRH19Z868STA0



Thermogel technology. No electrical power supply.

This sheet preserves the model specifications and operating conditions from the V1/2023 source.

LENS

MATERIAL	SUS 304
THICKNESS (MM)	0.9
TOLERANCE (MM)	+/- 0.05
REFLECTIVITY	> 60%
RADIUS (R')	3000
TOLERANCE	+/- 5%
FIELD OF VISION - RANGE (L~U MM)	770~800 (X) 570~600 (Y)
TOLERANCE (MM)	- 30

Saline mist resistant as per test report num 28109082 001 dated 01/04/2016

FRAME AND BACK PANEL

MATERIAL	Aluminium / ebond
REFLECTIVE MATERIAL	3M™ Diamond Grade™ DG3 Reflective Sheets Series 4000 / rosso

THERMOGEL TECHNOLOGY

- It prevents and limits ice formation on the lens surface.
- The thermoactivated gel in between the lens and the back panel regulates lens surface temperature according to environmental temperature and conditions.
- No eletric connection required.
- Operation depends on external environmental conditions and may be limited by excessive humidity, lack of exposure to sunlight, temperature below - 20°C.

UNIT WEIGHT

KG	18.00
----	-------

SUPPORTS

MATERIAL	Mild Steel
COATING	Hot Dip Galvanized (HDG)
POLE DIAMETER (MM)	60 or 76
WEIGHT (KG)	Ø 60 = 1,12 Ø 76 = 1,25

Source information and conditions

Indicative data, subject to possible unilateral changes. The weights are indicative and not binding. Picture for reference only.

Steel Crafts Europa s.r.l. Societa' con Socio Unico soggetta alla direzione ed al coordinamento di Ni Hsin Resources Bhd
Via Stretta Nr. 63 25070 Sabbio Chiese (BS) ITALY
CAP.SOC. € 10.000,00 I.v. REA: BS – 513499
Registro Imprese di Brescia e C.F. n. 03198560983
Part. IVA IT 03198560983
Tel.: +39.0307640079
Www.steelcrafts.it e-mail: info@steelcrafts.it

Technical data and references retained from the supplied V1/2023 sheet. The new graphic edition does not constitute a technical-data update.